

EC220AE9055



**VARIABLE EXTERNAL ANGLE DIM.
90X55 mm**

Trunkings > Wall and ceiling > Wiring device trunkings > Series kuadra - for 45x45 devices > Outer bend for device installation trunkings

Technical Symbols/Marks/Approvals



Norms

EN 50085-1 EN 50085-2-1

Description

Variable external angle for direction changes from 60° to 120°. Snaps onto the channel. Consists of two pieces.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000872 - Outer corner for wall duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Acrylonitrile butadiene styrene (ABS)
Halogen free	Yes	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Impact strength	IK08	Width	90 mm
Depth	55 mm	Model	Moulded hood	RAL-number	9001
Mounting method cover	Spanned	With protective foil	No	Working temperature	-5-60 °C
With cable fixing clip	No	With duct connector	Yes	Bottom perforation	No
Angle	60-120 °	Number of covers	1	Cover width 1	90 mm
Symmetric	Yes				

Documentation available for download

Certification

LICENCE 669929
KUADRA.pdf

Barcode



8033576779003

Unit

1 NR

0.14 [kg]



8059307212892

Cardboard

10 NR

0.39x0.295x0.15 [m]

1.4 [kg]