

**ECCAP5012B**



**FLOOR CABLE TRUNKING WITH COVER mm 50X12 WHITE - 3 COMPARTMENTS**



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Trunkings > Wall and ceiling > Solid cable trunkings > Series cap - floor trunkings > Floor mount trunkings

**Technical Symbols/Marks/Approvals**

IP40	IK08	UL94 V0	GWT 960°	RoHS II	CE	MADE IN ITALY
------	------	------------	-------------	---------	----	---------------

**Norms**

EN 50085-1 EN 50085-2-1

**Description**

Floor trunking made of self-extinguishing rigid PVC technopolymer. Impact resistance: 6J. Base designed for silicone adhesive fixing and perforated for screw and plug fixing. Wrap-around cover, removable only with tools. Trampling-resistant, load capacity 0.4 kg/cm².

**Etim**

**GROUP EG000006 - Installation ducts for wall and ceiling**

**CLASS EC000722 - On-floor installation duct**

<b>Degree of protection (IP)</b>	IP40	<b>Material</b>	Plastic	<b>Material quality</b>	Other
<b>Halogen free</b>	No	<b>Anti-bacterial treatment</b>	No	<b>Colour</b>	White
<b>Impact strength</b>	IK07	<b>Width</b>	50 mm	<b>Height</b>	12 mm
<b>Length</b>	2 m	<b>RAL-number</b>	9001	<b>Working temperature</b>	-5-60 °C
<b>Number of channels</b>	3	<b>With cover cap</b>	No	<b>Permitted cable diameter</b>	6-10 mm
<b>Bottom perforation</b>	Yes	<b>Slotted hole</b>	Yes	<b>With fixation</b>	No
<b>Demountable</b>	Yes	<b>Self-adhesive</b>	No	<b>Sealing lip</b>	Yes
<b>With anti-slip layer</b>	No	<b>Reflective</b>	No	<b>Fuel- and oil resistant</b>	No
<b>Resistance to vertical load applied in a small surface according IEC 61084-2-2</b>	1000 N	<b>Resistance to vertical load applied in a large surface according IEC 61084-2-2</b>	7000 N	<b>Suitable for car</b>	No
<b>Suitable for truck</b>	No	<b>Bending strength</b>	Rigid		

## Barcode



8050880886746

**Cardboard**

50 MT

0.195x0.102x2.025 [m]

13.5 [kg]